

PRODUCT: SAFETY SPECTACLES

REF. NO.: ES 005

DOC. NO.	QF/RD/05
ISSUE	01
REVISION	03
DATE	26 June 2015



CONFORMING TO IS 5983, EN 166 AND ANSI Z87.1

1	GENERAL PARAMETERS	TYPE	Spectacles
		DESIGN	Framed, Wraparound Spectacle Adjustable Temple Length Flexible Nose Pad and Temples
		APPLICATION	All Industrial Environment where Dust/Flying Particles Protection or Ultraviolet Protection is required
		LENS COLOUR OPTIONS	Clear, Smoked
		MECHANICAL HAZARD PROTECTION	Frontal, Lateral Impact Resistance Lateral Protection
		OPTICAL HAZARD PROTECTION	99.9% UV Protection
		MATERIALS	Lens – Polycarbonate Frame – Special Grade Nylon Nose Pad - PVC
		OPTICAL CLASS	Class I (Clear & Smoked) Scale for ES005(Clear) – 3 - 1.2 Scale for ES005(Smoked) – 5 - 2.5
		COATINGS	Available in two options: Hard Coated (Scratch Resistant) Antifog Coated (Fog Resistant)

2	VITAL TEST COMPLIANCE (It Conforms to all the Mandatory Requirements as per IS , CE & ANSI)		Resistance to Low Impact Energy of High Speed Particles at Extremes of Temperature Withstands the impact of a 6mm nominal diameter steel ball, weighing 0.86 gm at a speed of 45 m/s. The impacts are carried out after conditioning the eyewear to temperatures of $(55 \pm 2) ^\circ\text{C}$ and $(-5 \pm 2) ^\circ\text{C}$ Also withstands the impact of a 22mm nominal diameter, weighing 44gm. When dropped from a height of 1.27 – 1.31 mtrs.
		MECHANICAL HAZARD PROTECTION	
		OPTICAL HAZARD PROTECTION	99.9% UV Protection
		OPTICAL POWER	Zero Power Lens Spherical Refractive Power within ± 0.06 Dioptr Astigmatic Refractive Power within 0.06 Dioptr
		CORROSION RESISTANCE	No Corrosion observed on metal parts of Spectacle when tested as per IS, CE & ANSI Standards.
		RESISTANCE TO IGNITION	Spectacle did not ignited when tested as per ISI, CE & ANSI Standards.